

KAMOSHIELD

Exterior Emulsion



PROPERTIES



Economical Exterior Emulsion



Suitable for Dry & Humid Climate



It comes with 3 year Warrantee



High SRI Value



PRODUCT INFORMATION

Kamoshield is a wall coating paint for exterior walls. The acrylic co-polymer emulsion, based wall coating is best for application on exterior in dry or moderately humid areas. This coating has excellent addition to different types of surfaces like cement plasters, concrete, asbestos etc.



**3* Years
Warranty**

USP

Kamoshield is Economical Exterior Emulsion which comes with 3 years Warrantee. It is very suitable for Dry & Humid Climate. It also has High SRI Value which means it is durable product. The dry film of Kamoshield exhibits excellent resistance to chalking, flaking and weathering

Washability: Medium

Colors Available: 2500+

Coverage: 1 Coat (12-14 sq. m/lit. **), 2 Coat (7-9 sq. m/lit. **)



LEAD FREE GUARANTEE



FINISH- MATT & SMOOTH



3* Years
Warranty

AVAILABLE PACKS

1 Litre



4 Litres



10 Litres



20 Litres



AVAILABLE PACKS

Do not over thin.

Stir well and strain before use.

Always ensure paint those areas which are vertical to rain fall e.g., Top surfaces of sun shades.

THINNING

Apply one coat of Kamoprime exterior primer by thinning 1 Liter of primer with 500-600ml of water. Allow the primer coat to dry for 4 hours. Apply 2-3 coats by diluting 1 Liter of Kamoshield exterior emulsion Max. 750ml of water. A gap of 4-6 hours should be given between the coats.



TECHNICAL DATA

Finish	Smooth
Drying Time	4-6 hours
Flash Point	NA
Stability of Thinned Paint	To be used within 24 hours.
Shelf Life	3 years from the date of manufacturing in original tight containers kept away from direct sunlight and extreme heat.



**3* Years
Warranty**



— EXCELLENT DURABILITY —
UNDER EXTREME ADVERSITY!



ENVIRONMENT
FRIENDLY



HIGH
PERFORMANCE



SUSTAINABLE
BUILDING

