

KAMOSTAR

PERFORMANCE QUALITY
EXTERIOR PAINT



KAMOCEM

EMULSION
FOR EXTERIOR & INTERIOR WALLS



RECOMMENDED PAINTING SYSTEM

- ▶ **How to Prepare the Surface:** Clean the surface with a wire brush to remove loose paint, dust, grease, algae and fungus. After that, wash the surface down with Kamo Biowash to prevent reoccurrence of microbiological growth.
- ▶ **Smoothing the Surface:** Kamocare/ Kamoplast wall putty is recommended for leveling & smoothing the surface. It is effective in removing holes, dents, cracks and minor undulations. Larger cracks may be filled with a mixture of white cement and sand in the ration of 1:3.
- ▶ **Priming:** If the surface is highly absorbent, then, once Kamocare/ Kamoplast wall putty is to be applied, you may use Kamo Exterior Sealer. In the case of a fresh surface or repainting surfaces, apply one coat of Kamoprime Exterior Primer in the ration of 1:1.
- ▶ **Top Coat :** Apply 2 to 3 coats of Kamostar by diluting 1 litre of Paint with 500 to 600 ml of water. Or apply 2 to 3 coats of Kamocem by diluting 1 kg of Paint with 450 ml to 500 ml of water. Keep an interval of 4 to 6 hours between the two coats. An additional coat is required for dark shades and horizontal surface like window tops & ledges, etc.

PRECAUTION

- 01 For freshly plastered surfaces three months are required for curing before the painting of the walls.
- 02 For highly absorbent and chalky surfaces Kamo Exterior Sealer is recommended.
- 03 Paint procedure should not be applied on continuous seeping & damp surface.
- 04 Use of Kamdhenu Exterior Primer is mandatory for all exterior paint surfaces.
- 05 Use Kamdhenu Waterproofing System before painting on the seepage and damp surfaces.



LOW VOC



LEAD FREE



ECO-FRIENDLY

Dreamz
Colour
DL Ke Rang Deewaron Pe

KAMDHENU LIMITED

2nd Floor, Building No. 9A, DLF Cyber City, Phase-III, Gurugram (HR.)-122002

Fax: 0124-4218524, Email: kamdhenu@kamdhenulimited.com

+91-124-4604500 (30 Lines) Toll Free: 1800 1800 545

www.kamdhenupaints.com



Shade
SELECTION

KAMOSTAR EMULSION

Popular Exterior Vibrant Shades

	
PASSION YELLOW KS 0067	MATRIX GREEN KS 0065
	
GOLDEN GLOW KS 0068	FANTASY GREEN KS 0066
	
PAPAYA YELLOW KS 0069	LAPIS LAZULI KS 0078
	
VIBRANT ORANGE KS 0073	ROYAL BLUE KS 0020
	
BOUGAINVILLEA KS 0070	MING RED KS 0042
	
NUT BROWN KS 0040	TERRACOTTA KS 0061

Shades are shown for indication purpose only.

KAMOCEM EMULSION

Popular Cement Paint Shades

	
IVORY KC 0005	NEW PALE ROSE KC 0020
	
MIDCREAM KC 0008	PEACH KC 0016
	
LIGHT BISCUIT KC 0012	AQUAMARINE KC 0028
	
DHOLPUR STONE KC 0015	APPLE GREEN KC 0035
	
PINK KC 0021	TERRACOTA KC 0022
	
CANDY PINK KC 0018	GOLDEN BROWN KC 0036

Shades are shown for indication purpose only.

KAMOSTAR

PERFORMANCE QUALITY EXTERIOR PAINT



ECONOMICAL EXTERIOR EMULSION

SUITABLE FOR DRY & HUMID CLIMATE

Available in 20 ltr, 10 ltr, 4 ltr & 1 ltr.

KAMOCEM EMULSION

FOR EXTERIOR & INTERIOR WALLS



- ECONOMICAL DUAL EMULSION
- EMULSION FINISH ON COST OF CEMENT PAINT
- NO CURING IS REQUIRED
- SAVE WATER - SAVE EARTH

Available in 10 kg. & 5 kg.