

VELVETY

Interior Emulsion



PROPERTIES



Silky Touch



High Opacity



Rich Sheen



Stain Resistance



Low VOC





PRODUCT INFORMATION

Velvety Luxury Interior Emulsion is water based, 100% acrylic Interior Wall Finish, it provides a Silky Sheen Finish which lends a soft regal glow to the interiors of the room. It has excellent flow giving a near brush mark free finish. It is suitable for plaster walls, POP surface etc.



USP

It is a premium quality interior emulsion with a Rich Luxury Pearl like finish. It is High in durability and with also very high in cleanability because of the presence of fine polysiloxane. It is Rich in Sheen and also offers High Stain Resistance quality as a result it is very easy to clean and maintain the new look of walls for years

Washability: Best in Class

Colors Available: 2500+

Coverage: 1 Coat (20-24 sq. m/lit. **), 2 Coats (11-12 sq. m/lit. **)



LEAD FREE GUARANTEE & LOW VOC



FINISH- LOW SHEEN & SMOOTH



AVAILABLE PACKS

1 Litre



× >>>>>>

4 Litres



10 Litres



20 Litres





PAINT APPLICATION PROCESS

Application	Thinner	Dilution % (by volume)	Recoated Period (hours)
Step 1 Kamdhenu Paints wall putty	WATER	Approx. 35-40 % of water (by wt.)	4 HRS
Step 2 INTERIOR WALL PRIMER BRUSH / SPRAY / ROLLER	WATER	BRUSH 50 – 60 SPRAY 30 – 40 ROLLER 50 - 60	4 HRS

Horizontal surface like top of window, ledges should be painted with 3 coat of Velvety for greater protection



APPLICATION OF PRIMER IS MANDATORY

STEP 3 FIRST COAT VELVETY BRUSH / SPRAY / ROLLER	WATER	BRUSH MAX 45 SPRAY MAX 45 ROLLER MAX 45	4 - 6 HRS
STEP 4 SECOND COAT VELVETY BRUSH / SPRAY / ROLLER	WATER	BRUSH MAX 45 SPRAY MAX 45 ROLLER MAX 45	4 - 6 HRS



SURFACE PREPARATION

Ensure the plaster is completely dry and thoroughly clean & free from dust, flake, grease etc. And make sure that all water leakage, seepage are repaired before painting. For old pre-painted surfaces remove all loosely adhering powdery materials of defective paints by thoroughly brushing, scrapping and water jetting. If required, for best performance it is recommended to apply one coat as a priming coat of Velvety diluted 1:1 with water for any kind of surface.



THINNING

Apply one coat of kamoprime interior primer by thinning 1 Ltr of primer with 500-600ml of water. Allow the primer coat to dry for 4 hours. Apply 2-3 coats by diluting 1 Ltr of Velvety interior emulsion Max. 450ml of water. A gap of 4-6 hours should be given between the coats.



PRECAUTIONS

Do not over thin.
Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
Stir well and strain before use.
Tint using Kamdhenu Machine Colorants only.
Always ensure paint those areas which are vertical to rain fall e.g., Top surfaces of sun shades.



SAFETY, HEALTH AND INFORMATION

Keep container tightly closed and keep out of reach of children. A suitable cartridge mask should be worn when rubbing down. Ensure good ventilation during application & drying. Do not breathe vapor/spray. When applying paint, it is advisable to wear eye protection. In case of contact with eye, rinse immediately with plenty of water and seek medical advice, if required. Care must be taken when transporting paint. Keep container in a secure upright position. Stir thoroughly before use. It is eco-friendly paint.



TECHNICAL DATA

Finish	Smooth
Drying Time	4-6 hours
Flash Point	NA
Stability of Thinned Paint	To be used within 24 hours.
Shelf Life	3 years from the date of manufacturing in original tight containers kept away from direct sunlight and extreme heat.





Nothing feels better than a
velvet!



STAIN
RESISTANCE



SILKY TOUCH



LOW VOC

